

# SpeedStile BP

SpeedStile BP	SpeedStile BP BA	SpeedStile BP EV
Throughput (Proximity reader "Hands free")	Up to 40 ppm	Up to 40 ppm
Passage Width (mm)	550	550
Cabinet Width (mm)	300 - 480	300 - 490
Cabinet Length (mm)	1448 - 1932	1448 - 1932
Cabinet Height (mm)	950	950
Wide Lane Option (mm)	900	900
Cabinet Standard Finish	Metallic grey	Full stainless steel 304 grade
Top Lid Standard Finish	Painted polyurethane	Stainless Steel
Wing Housing Standard Finish	Painted steel to match lid	Stainless Steel
Optional Finishes	PMMA & Stainless Steel 8.5mm 3ply laminate safety glass Full Stainless Steel	PMMA & Stainless Steel 8.5mm 3ply laminate safety glass Full Stainless Steel
Reader Integration	X	X
Way Mode Indicators	X	X
LED Pictogram	Option	Option
RS485 interface	Option	Option
COMR1 switching interface	Option	Option
Digital LCD Counter	X	X
Emergency Break Glass Push Button	X	X
Bi-Directional Passage	X	X
Piggybacking Detection	X	X
Tailgating Detection	X	X
Intrusion Detection	X	X
Wrong Way Detection	X	X
Leave Aisle Timeout	X	X
Fail Safe Manual Push Opening	X	X
Fail Safe via Battery Back Up Option	X	X
MTTR	< 30 Minutes	< 30 Minutes
IP Rating	IP 20	IP 20
Noise Level	< 55dB <sup>3</sup>	< 55dB <sup>3</sup>
MCBF	4 Million (5 Million if NO) Cycles	4 Million (5 Million if NO) Cycles