

# SpeedStile FP

| SpeedStile FP                              | SpeedStile FP BA   | SpeedStile FP EV   | SpeedStile FP Glide   |
|--|--|--|---|
| Throughput (Proximity reader "Hands free") | Up to 40 ppm   | Up to 40 ppm   | Up to 40 ppm  |
| Passage Width (mm)                         | 550  | 550  | 550   |
| Cabinet Width (mm)                         | 300 - 480  | 300 - 490  | 320   |
| Cabinet Length (mm)                        | 1448 - 1932  | 1448 - 1932  | 1495  |
| Cabinet Height (mm)                        | 950  | 950  | 900   |
| Wide Lane Option (mm)                      | 900  | 900  | 900   |
| Glass Heights (mm)                         | 1200 - 1800  | 1200 - 1800  | 900 - 1800  |
| Telescopic Mechanism for Wide Lanes        |  |  | X   |
| Cabinet Standard Finish                    | Metallic grey Polyurethane PUR painted                                       | Full stainless steel 304 grade   | Powder coated steel with anodised aluminium inlays  |
| Top Lid Standard Finish                    | Painted polyurethane   | Stainless Steel  | Powder coated steel   |
| Side Panels Standard Finish                | Acrylic and stainless steel  | 8.5mm 3 ply laminate safety glass  | Powder coated steel with anodised aluminium inlays  |
| Optional Finishes                          | PMMA & Stainless Steel 8.5mm 3ply laminate safety glass Full Stainless Steel | PMMA & Stainless Steel 8.5mm 3ply laminate safety glass Full Stainless Steel | Powder coated RAL colours, Corian®, laminates, wood finishes                                  |
| Dynamic user interaction pack              |  |  | Additional user guidance by visual and audio cues & dynamic LED strip lighting & audio driver |
| Reader Integration                         | X  | X  | X   |
| Way Mode Indicators                        | X  | X  | X   |
| LED Pictogram                              | X  | X  | X   |
| Digital LCD Counter                        | X  | X  |   |
| Emergency Break Glass Push Button          | X  | X  |   |
| Bi-Directional Passage                     | X  | X  | X   |
| Piggybacking Detection                     | X  | X  | X   |
| Tailgating Detection                       | X  | X  | X   |
| Intrusion Detection                        | X  | X  | X   |
| Wrong Way Detection                        | X  | X  | X   |
| Climb over / under Detection               |  |  | X   |
| Leave Aisle Timeout                        | X  | X  | X   |
| Fail Safe Manual Push Opening              | X  | X  |   |
| Anti-crawling flap leaf barrier            | X  | X  |   |
| Battery Back-up                            | For 1 last operating cycle   | For 1 last operating cycle   |   |
| MTTR                                       | < 30 Minutes   | < 30 Minutes   | < 30 Minutes  |
| IP Rating                                  | IP 20  | IP 20  | IP 20   |
| MCBF                                       | 4 Million (5 Million if NO) Cycles   | 4 Million (5 Million if NO) Cycles   | 10 Million Cycles   |